

CONSTRUCTION TAPES

THE FINAL STEP FOR MAXIMUM REDUCTION OF AIR INFILTRATION THROUGH WALL SYSTEMS IS TO HELP CREATE A SEAMLESS, PROTECTIVE ENVELOPE SEALED WITH THE DUPONT™ TYVEK® RANGE OF TAPES.



1310B BUTYL TAPE

ROLL WIDTH	50mm
ROLL LENGTH	30m
ROLL WEIGHT	2.8 kg

Double sided butyl based sealant, used to form a water and airtight seal between the Tyvek® membrane and most commonly used building materials. Compatible with brickwork, block work, masonry, timber, metalwork and most plastic.

FLEXN FLEXWRAP™ NF

ROLL WIDTH	152mm /228mm
ROLL LENGTH	23m
ROLL WEIGHT	tba
FACE SHEET	Polyethylene laminate (white)
ADHESIVE	Butyl rubber (black)
THICKNESS	64 mil (1,620 microns)
RELEASE LINER	Heavy-duty siliconized paper

Flexible sealant tape for round or custom shaped windows, 3-D sill protection and wall interruptions e.g. dryer vents, hose bibs. Can be used on substrates where fasteners cannot be applied, corner pieces for sills and the head of recessed windows.

2060B TYVEK® TAPE

ROLL WIDTH	75mm
ROLL LENGTH	25m
ROLL WEIGHT	0.66kg

Single-sided Tyvek® tape for sealing overlaps and making good around penetrations, pipes and windows. The adhesive is acrylic based, which once cured provides a very durable and long lasting bond. Maximum UV exposure of 3 months.

